

New England Multiline

MADE IN 

New England Multiline has the same 3-strand composite construction as Multiline II, constructed by twisting three strands of a blend of spun and filament polyester around cores of fibrillated polyolefin. In addition, New England Multiline uses block creel fibers making it very grippy and therefore also CI-1805 compliant. Having met the requirements for CI-1805 compliance it is also fully certified as a Life Safety Rope per the Association for Challenge Course Technology (ACCT) standards.



Features


- ✓ Block creel fibers for enhanced grip
- ✓ Polyolefin cores for improved abrasion resistance and handling
- ✓ CI-1805 compliant Life Safety 3-Strand Rope
- ✓ Fully certified as Life Safety Rope per ACCT (Association for Challenge Course Technology) standards

Specifications

Material: Polyolefin
Polyester

Standard: CI-1805
ACCT

Braid: 3



All diameters



Ø		Weight		Min. breaking strength Free length	
mm	inch	g/m	lbs/100'	daN	lbf
8	5/16	39.6	2.70	825	1,860
10	3/8	62.5	4.20	1,290	2,900
11	7/16	77.4	5.20	1,775	4,000
12	1/2	99.7	6.70	2,265	5,100
16	5/8	154.7	10.40	3,780	8,500
19	3/4	215.7	14.50	4,490	10,100
22	7/8	266.3	17.90	5,780	13,000
25	1	313.9	21.10	6,895	15,500
28	1 1/8	447.8	30.10	9,340	21,000

Multiline II

MADE IN 

Multiline II is a composite rope, constructed by twisting three strands of a blend of spun and filament polyester around cores of fibrillated polyolefin. The polyolefin keeps the strands firm and round without adding weight, which improves abrasion resistance and handling. The spun polyester gives Multiline II its characteristic fuzzy feel and makes it easier to grip, even when wet. Multiline II provides the greatest durability, highest strength, lightest weight, and most consistent supple feel over time of any commercially available composite rope. Multiline II is easily identified by its familiar two orange markers.



Features

- ✓ Improved grip and knot holding even when wet
- ✓ Fibrillated polyolefin cores for firm and round hand
- ✓ Consistently supple feel over the service life of the rope
- ✓ Great for natural crotch rigging

Specifications

Material: Polyolefin
Polyester

Braid: 3



All diameters



Ø		Weight		Min. breaking strength Free length	
mm	inch	g/m	lbs/100'	daN	lbf
8	5/16	39.6	2.66	825	1,860
10	3/8	62.5	4.20	1,290	2,900
11	7/16	77.4	5.20	1,775	4,000
12	1/2	99.7	6.70	2,265	5,100
16	5/8	154.7	10.40	3,780	8,500
19	3/4	215.7	14.50	4,490	10,100
22	7/8	266.3	17.90	5,780	13,000
25	1	313.9	21.10	6,895	15,500
28	1 1/8	447.8	30.10	9,340	21,000